

FEEDLINE REPLACEMENT INSTRUCTIONS FOR THE BOND-A-MATIC™ DISPENSING SYSTEM

IMPORTANT: READ INSTRUCTIONS CAREFULLY BEFORE ATTEMPTING TO CHANGE THE FEEDLINE.

At the first sign of stress or kinking of the product feedline, the entire line should be replaced. To change the line use the following procedure:

- { Turn the Bond-A-Matic 2000 Reservoir "Off" and release all of the pressure within the tank by depressing the toggle valve on the reservoir cover.
- { Raise the applicator above the reservoir with the nozzle in the vertical up position and depress the Gluematic™ Tip or the lever on the Vari- Drop™ Applicator. This will allow the product in the feedline to drain back into the bottle in the reservoir.
- { Unscrew the nut on the back end of the applicator and remove the applicator from the feedline.
- { Remove the cover from the reservoir and unscrew the brass nut from the tank fitting. Remove the old feedline from the tank fitting.
- { The new feedline consists of a length of white Polyethylene tubing that can be cut to the required length.
The new feedline for dispensing UV products will consist of a length of black Polyethylene tubing that can be cut to required length.
- { Slide a spring guard, the brass nut, and the plastic ferrule for the tank fitting over the tubing.
- { Insert the end of the tube through the tank fitting so that the ferrule and nut can be secured to the fitting. The tube should extend 7" (175mm) below the bottom side of the reservoir cover.
- { Attach the other end of the feedline to the applicator in the same manner with the plastic nut and sleeve. Note: Apply a liberal amount of Silicone Grease to the threads on the applicator before securing it to the feedline.
- { The system is now ready for use. Secure the cover on the reservoir. Turn the pressure regulator all the way counter clockwise until it stops rotating. Place the toggle switch in the "On" position. Adjust the reservoir pressure to 2 PSI. Check to make certain that there is no product leakage at the feedline connections.

ORDERING INFORMATION:

<u>Part Number</u>	<u>Description</u>
997562	Feedline Replacement Kit (4 feet long)
997563	Feedline Replacement Kit (8 feet long)
997564	Feedline Replacement Kit (12 feet long)
997565	Feedline Replacement Kit (12 feet long for UV products)

Each kit contains (1) Plastic Ferrule, (1) Brass Tank Fitting Nut, (1) Feedline, (2) Spring Guards, (1) Plastic Nut and Sleeve, and (1) Gluematic Applicator Handle.



Rocky Hill, CT 06067

Loctite is a Registered Trademark and Bond-A-Matic, Vari-Drop, and Gluematic are Trademarks of Loctite Corporation, Rocky Hill, Connecticut 06067.